

AK SERIES

Door Release Button Series

General Description

Door release button can be used for momentary release of fail-safe or fail-secure electronic locks and widely used in door, gate, exit and automation control. It may also be used to input an exit signal to an access control system such as HID VertX or HID Edge networked access control system. The button is spring loaded and mounted on aluminium or stainless steel plate. The contacts switch when the button is depressed and return when released.

Key Features

- Can be mounted next to door
- Single gang or narrow stile
- Ideal for request-to-exit access control applications

AK-1R



- Contact type : NO
- Dimension : (L)86 x (W)50 x (H)20mm
- Aluminium panel and stainless steel button
- IP65
- Maximum current rating: 3A@36VDC

AK-1S



- Contact type : NO
- Dimension : (L)86 x (W)86 x (H)20mm
- Aluminium panel and stainless steel button
- IP65
- Maximum current rating: 3A@36VDC

AK-2R



- Contact type : NO
- Dimension : (L)91 x (W)28 x (H)20mm
- Stainless steel panel and stainless steel button
- IP65
- Maximum current rating: 3A@36VDC

AK-2S



- Contact type : NO
- Dimension : (L)86 x (W)86 x (H)20mm
- Stainless steel panel and stainless steel button
- IP65
- Maximum current rating: 3A@36VDC